

C40

IC-PNEUMATIC LPG/DIESEL
 8000 / 9000 / 10,000 / 11,000 lbs.
 (4000 / 4500 / 5000 / 5500 kg)



STANDARD SPECIFICATIONS

C40/45/50s/55s

Manufacturer's Designation		C40D	C45D	C50sD	C55sD	C40L	C45L	C50sL	C55sL
Load Capacity / Rated Load	lbs(kg)	8000 (4000)	9000 (4500)	10,000 (5000)	11,000 (5500)	8000 (4000)	9000 (4500)	10,000 (5000)	11,000 (5500)
Height Overhead Guard	in(mm)	91.5 (2324)	91.5 (2324)	90.4 (2226)	90.4 (2226)	91.5 (2324)	91.5 (2324)	90.4 (2226)	90.4 (2226)
Width	in(mm)	55.1 (1400)	55.1 (1400)	68.6 (1742)	68.6 (1742)	55.1 (1400)	55.1 (1400)	68.6 (1742)	68.6 (1742)
Right Angle Stack (add load length & clearance)	in(mm)	134.5 (3416)	135.9 (3451)	141.9 (3605)	144.4 (3669)	134.5 (3416)	135.9 (3451)	141.9 (3605)	144.4 (3669)
Outside Turning Radius	in(mm)	111.9 (2843)	113.3 (2878)	119.4 (3032)	120.9 (3071)	111.9 (2843)	113.3 (2878)	119.4 (3032)	120.9 (3071)
Travel speed loaded / unloaded	mph (kph)	15.5 (25.0) / 16.2 (26.0)	15.4 (24.8) / 16.2 (26.0)	14.9 (24.0) / 15.8 (25.5)	14.9 (24.0) / 15.8 (25.5)	12.6 (20.2) / 13.4 (21.5)	12.4 (20.0) / 13.4 (21.5)	13.5 (21.7) / 12.4 (20.0)	13.5 (21.7) / 12.4 (20.0)
Engine / Rated output per SAE J1349	HP(KW) @ rpm	Kubota/92(68.6)@2400	Kubota/92(68.6)@2400	Kubota/92(68.6)@2400	Kubota/92(68.6)@2400	GM/92.5(69)@2400	GM/92.5(69)@2400	GM/92.5(69)@2400	GM/92.5(69)@2400

STANDARD FEATURES

Available with 3.8 L Turbo Charged Kubota Diesel Engine or 4.3 L V-6 GM LPG Engine • Spacious Operator Compartment • Fully Adjustable, Full Suspension Seat • Simple & Error Proof Parking Brake • Wet Disc Brakes on ALL Models • Rugged Upright and Carriage • “Built to Last”[®] Chassis



For more information on this model and the full line of CLARK Forklifts, find your local CLARK Dealer at www.clarkforklifts.co.za.